Docket 5000-1-506

## IN THE CLAIMS:

Please amend the claims as follows:

1. (Currently Amended) A wavelength-division-multiplexed passive optical network comprising:

a central office in which a multi-wavelength lasing source is located, said multi-wavelength lasing source having a multiplexing/demultiplexing unit and a plurality of reflectors comprised of mirrors coupled to the multiplexing/demultiplexing unit to reflect demultiplexed signals back to the multiplexing/demultiplexing unit;

a plurality of subscriber terminals for transmitting an upward signal using a reflected signal of a multi-wavelength signal transmitted from the central office; and

a local office disposed between the central office and the subscriber terminals via optical fibers for demultiplexing the multi-wavelength signal transmitted from the central office and for multiplexing signals from each of the subscriber terminals.

2. (Currently Amended) A wavelength-division-multiplexed passive optical network as claimed in claim 1, wherein the central office comprises:

a first optical amplifier for generating amplified spontaneous emission noise;
the multiplexing/demultiplexing unit having a first input/output terminal and a
plurality of upward signal output terminals at a first side portion so as to receive the
amplified spontaneous emission noise and to output a multi-wavelength lasing light, and
a plurality of second input/output terminals and an upward signal input terminal for a
multi-wavelength lasing light generation at the first side portion so as to output a multiwavelength lasing light multiplexed in response to the input of the amplified spontaneous

Docket 5000-1-506

emission noise and to demultiplex and to output the upward signal in response to the input of the upward signal;

a plurality of upward signal receivers coupled to the upward signal output terminals at the first side portion of the multiplexing/demultiplexing device-unit in one-to-one correspondence;

the plurality of reflectors is coupled in one-to-one correspondence to the second input/output terminals at the second side portion of the multiplexing/demultiplexing unit, so as to input-for reflecting said demultiplexed signals outputted through the second input/output terminals back to the second input/output terminals; and

a circulator for outputting a multi-wavelength lasing light inputted from the multiplexing/demultiplexing device to the local office and transmitting an upward signal inputted from the local office to the upward signal input terminal of the multiplexing/demultiplexing unit.

- 3. (Previously presented) A wavelength-division-multiplexed passive optical network as claimed in claim 2, wherein the multiplexing/demultiplexing unit is an N×N waveguide grating router.
  - 4. (Cancelled).
- 5. (Previously presented) A wavelength-division-multiplexed passive optical network as claimed in claim 2, wherein the central office further comprises an external modulator for modulating a multi-wavelength lasing light outputted from the

12012269246

Docket 5000-1-506

multiplexing/demultiplexing unit on the basis of predetermined broadcasting service signals and for outputting the modulated signal to the circulator.

- (Original) A wavelength-division-multiplexed passive optical network as claimed in claim 5, wherein the external modulator is a LiNbO3 modulator.
- (Original) A wavelength-division-multiplexed passive optical network as 7. claimed in claim 5, wherein the external modulator is an electro-absorption modulator.
- (Original) A wavelength-division-multiplexed passive optical network as 8. claimed in claim 5, wherein the external modulator is a semiconductor optical amplifier.
- (Original) A wavelength-division-multiplexed passive optical network as claimed in claim 1, wherein the subscriber terminal includes a reflective optical amplification means.
- (Original) A wavelength-division-multiplexed passive optical network as claimed in claim 9, wherein the reflective optical amplification means is a reflective semiconductor optical amplifier.

Docket 5000-1-506

- 11. (Original) A wavelength-division-multiplexed passive optical network as claimed in claim 10, wherein the reflective semiconductor optical amplifier comprises an anti-reflection coating face formed on one side, a high-reflection coating face formed on another side, and a gain medium formed between the anti-reflection coating face and the high-reflection coating face, so that the semiconductor optical amplifier total-reflects a signal inputted through the anti-reflection coating face by the high-reflection coating face and outputs the total-reflected signal.
- 12. (Previously presented)A wavelength-division-multiplexed passive optical network as claimed in claim 11, wherein the semiconductor optical amplifier further amplifies and modulates the signal when the signal passes the gain medium.
- 13. (Original) A wavelength-division-multiplexed passive optical network as claimed in claim 9, wherein the subscriber terminal further comprises an optical distributor and a broadcasting data optical receiver so as to receive a broadcasting service signal, the optical distributor distributing downward signals inputted from the local office to the reflective optical amplification means and the broadcasting data optical receiver.
- 14. (Currently Amended) A wavelength-division-multiplexed passive optical network as claimed in claim 1, wherein the lasing source comprises:
  - a laser diode;
  - a circulator;
  - a first and second optical distributor;
- a first optical amplifier coupled to the circulator and first and second optical distributor;

Docket 5000-1-506

- a\_\_\_multiplexer/demultiplexer\_device\_said\_multiplexing/demultiplexing\_unit coupled to the circulator;
  - a plurality of mirrors coupled to the multiplexer/demultiplexer device; and a filter coupled to the circulator and a second optical amplifier.
- 15. (Currently Amended) A wavelength-division-multiplexed passive optical network as claimed in claim 14, wherein the lasing source further comprises an upward data receiver coupled to the multiplexer/demultiplexer devices aid multiplexing/demultiplexing unit.
- 16. (Currently Amended) A wavelength-division-multiplexed passive optical network as claimed in claim 14, wherein the lasing source further comprises a second circulator coupled to plurality of mirrors said multiplexing/demultiplexing unit, the second optical distributor and the local office.
- 17 (Previously Presented) A wavelength-division-multiplexed passive optical network as claimed in claim 16, wherein an external modulator is coupled between the second circulator and the second optical distributor.
- 18. (Previously Presented) A wavelength-division-multiplexed passive optical network as claimed in claim 9, wherein the subscriber terminal further comprises:

a broadcast reception optical receiver; and

an optical distributor coupled to the a reflective optical amplification means, the broadcast reception optical receiver and the local office.